



# MICRO IP CAMERA



## STORE AND FORWARD 2.1 MP IP CAMERA FOR COVERT SURVEILLANCE WITH 3G/ WI-FI\* SUPPORT

Miniature size, hi-res live view with sound and video recording for later upload over the Internet makes this camera a perfect solution for law enforcement agencies or companies which need to control working areas, offices, warehouses and so on. The camera can be also used for a hidden car installation.

This 2.1MP IP camera connects to a network with a regular LAN cable or via a Wi-Fi/3G\* transceiver. Video can be recorded to the internal DVR with micro SD slot (32GB) or to any connected NVR or DVR. It is also equipped with an additional analog (PAL/NTSC) output for monitor or other analog devices connection.

There is an Android app supporting camera's live view and records review.

### FEATURES:

- ONVIF 1.02 Support
- Motion detection, schedule or remote command recording modes
- Digital Day & Night modes
- Pinhole or 3.7mm/F2.5 Board Lens
- Micro SD/SDHC card (Max 32GB)
- Dual Streaming (H.264 & MJPEG)
- DC12V / PoE (IEEE 802.3af)
- Optional Wi-Fi module
- Optional 3G module



### PRODUCT SPECIFICATIONS

ITEM	DESCRIPTION	
Image Device	2.1 Mega Pixel 1/3" SONY Progressive CMOS	
Lens(Unit: mm)	Board Lens, Pinhole Lens	
Minimum Illumination	Color: 0.625 lux, B/W: 0.31 lux	
Video	Video Codec	H.264 Main Profile Motion JPEG
	Resolutions (H.264/MJPEG)	H.264: MAX 1920x1080 + Analog Output @ 30fps, MJPEG: MAX 1280x720 @30fps
	Video Streaming	Simultaneous Motion JPEG and H.264, Controllable frame rate and bandwidth Constant and variable bit rate (H.264)
	Image Settings	Brightness, Contrast, Saturation, Sharpness, White Balance, Exposure Control, Back Light Compensation Compression levels : 100 (Motion JPEG) Viewer Magnification : 0.5x, 1x, 1.5x, 2x Overlay capabilities : time, date, text, privacy mask
Audio	Audio Code	G. 711, G.726
Network	Security	Multiple user access levels with password protection, HTTPS (SSL)
	Supported Protocols	IPv4, HTTP, HTTPS, TCP, RTSP, RTP, UDP, IGMP, RTCP, SMTp, FTP, ICMP, DHCP, ARP, DNS, DDNS, HTTPS, UPnP
General	Power	DC12V(±10%), Max. 240mA/ Power over Ethernet Class 3 (IEEE 802.3af)
	Interfaces	RJ-45 for Ethernet 10baseT/100baseTX with PoE 3.5mm Power Input: DC 12V, connector for Service Video SD Card Socket, NTSC / PAL Toggle Switch
	Operating Conditions	Temperature: - 10°C ~ +50°C (14°F ~ 122°F), Humidity 20-80% RH (non-condensing)

\*Wi-Fi and 3G modules are sold separately and not included in the basic kit.