



C2 WALLABY

CDMA | GSM
CERTIFIED | CERTIFIED



verizon AND **GSM CAPABLE**
TACTICAL LIVE LISTENING FOR MULTIPLE CALLERS



Conference 
Tactical Support
Controller
Commander
Local Support

PEACE-OF-MIND FOR OFFICER AND UNDERCOVER SAFETY

Available cased or prepared for concealment and body-worn deployment, the C2 Wallaby Series provides live audio for up to five parties simultaneously. Officer safety, simple concealment and Geonautics quality over the air makes the C2 Wallaby the clear choice for covert live listening. C2d includes an integrated high quality Dingo recorder for storing the evidence and a 3 function key fob provides remote command over the power and recording functions and can initiate a call to a preset number for live audio or panic alarm. (model dependent)

- C2 is certified for use on the Verizon CDMA Network for maximum coverage in USA
- C2 will also operate on GSM networks worldwide (SIM required)
- Dual function quad-band modem
- Multiple live listening for outstanding Officer safety
- Link multiple calls on CDMA / Full conference calling on GSM (up to 5)
- High quality Geonautics audio
- Available cased or minimised for concealment
- One-touch fast start up - Simple to use - No software
- DTMF configuration
- PIN protected inbound calling
- Dingo recorder on board 4GB max (C2d, C2pd)
- Key fob remote commanding (C2d, C2pd) + Panic alarm
- Integrated battery (C2, C2d)



C2 Wallaby Product Specification



**Verizon Certified
for CDMA network**

**Officer safety
device for tactical
live-listening over
a cellular network**

**High performance
"Dingo" audio
recorder on-board**

**Internal
rechargeable
battery with fast
USB charge**

**Available in
External or
Internal mic
versions**



PROPERTY C2d	SPECIFICATION
Size Metric (mm)	104 x 48 x 12
Size Imperial (inches)	4.1 x 1.9 x 0.5
Storage Temperature	-20°C to 70°C / -4°F to 158°F
Operating Temperature	-5°C to 65°C / 23°F to 149°F
Operating Voltage	5v ± 0.25v (USB)
Operating Current: Sleep	0.5mA (500uA)
Operating Current: Recording	9mA
Operating Current: Registered *	35mA
Operating Current: On a Call*	125mA
Internal Battery	680mAh
Charge Time	1.5hrs (approx.)
Operation Time	3.5hrs (approx.)
Dynamic Range	48dB (theoretical), > 42dB typical 8 bit, >38dB typical 4 bit
Sample Rates	8kHz, 11kHz
Audio Bandwidth	200Hz - 3.2kHz (8kHz sampling), 200Hz - 4.7kHz (11kHz sampling)

**Varies on signal strength*

KIT C2d	CONTENTS
	C2d Device
	Microphone (1m/3ft cable)#
	USB Download Cable (1.2m/4ft cable)
	Stubby microphone#
	USB Charge Cable
	RF Keyfob (optional)
	USB Stick (Whisper2, Authenticate and User Guide)
	Plastic case

Not included in the "Internal Microphone" kit

RECORDING TIME (Typical)			
QUALITY	BITS	2GB	16GB
11kHz Mono	8 bit - PCM	2 days	18 days
8kHz Mono	8 bit - PCM	3 days	24 days

COMPATIBLE PRODUCTS (Sold Separately)	
APS - Audio	Server-based file management for Operations, Targets and Devices with 'Authenticate' Software

For North American Joey users ...
ask your supplier about the new JOEY-GSM Audio Intercept System.
A C2 Wallaby and Joey integrated into one modular package
providing cellular and a VHF transmitter for direct RF use.



Wallaby

verizon ✓



T-Mobile

